

# APEXA® GW

## Versatile Powerhouse™

- 装备最新的高性能Intel® Processor(三种, 可选择的)。
  - 零售商内顾客和店员用, 可以使用多用途解决办案。
  - 纤细和紧凑、小巧支架、现代造型。
- 19.5寸引领无边框平坦和大型显示器的PCAP触摸屏。
  - 多用 I/O综合可配件。
  - 立式和壁挂式的设计。
  - 很快安装和有用性。



GCOD DESIGN




## 事项&有点



### 新流行. 新设计

- 小巧的体积和小巧的机身
- 现代与当代的设计



### 装备最新的高性能Intel® Processor

- Intel® Core™ i5-6200U, Pentium® 4405U
- Intel® Celeron® J1900 Quad-Core



### 优秀的触摸屏

- 19.5寸引领无边框和平坦的触摸屏
- PCAP 触摸屏, LED背光源



### 在什么地方可以安装。

- 在柜台和 Wall Mount Kit可以安装。
- 可选择VESA (Option)



### 节约时间和费用

- 很容易接线 I/O 配件。
- 很快安装和有用性。



### 对所有接线

- 多用 I/O 综合可选配件。
- 6 USB, 5 Serial. 可选配件。

# 参数规格

General Specifications	
System	
Processor	Intel® Celeron® J1900 (2.0 GHz) Quad-Core Processor, Fanless Intel® Core™ i5-6200U Processor (3M Cache, 2.80 GHz) Intel® Pentium® Processor 4405U (2M Cache, 2.10 GHz)
Chipset	J1900 Intel® Bay Trail 6200U/4405U ITE Tech IT8786E
Memory	J1900 4GB Standard, DDR3L 1600 MT/s, Socket 1 x SODIMM 6200U/4405U 4GB Standard, DDR4L 2133 MT/s, Socket 1 x SODIMM (Max. 16GB)
Storage	J1900 SATA 2 (3Gb/s) 2.5 inch SSD 64GB, Support AHCI 6200U/4405U SATA 3 (6Gb/s) 2.5 inch SSD 64GB, Support AHCI
OS	Windows 7, Windows 8.1, Windows 10 IoT Enterprise, POS Ready 7
Audio	Realtek ALC662-VD
Display	
Type	19.5" Wide TFT LCD, LED Backlight
Resolution	1600 x 900
Brightness	250 cd/m <sup>2</sup> (typ.)
Touchscreen	Projective Capacitive Touch
Interface	
Display	1 x VGA (With Power Output)
USB	J1900 6 (Rear 2, Back 4, USB 2.0 x 6) 3 (Reserved for MSR, SCR, i-Button/Touch Controller/Camera), RJ-45 6200U/4405U 6 (Rear 2, Back 4, USB 3.0 x 2, USB 2.0 x 4) 3 (Reserved for MSR, SCR, i-Button/Touch Controller/Camera), RJ-45
Serial	(COM1 with 5V/12V Power Output on 9 Pins, BIOS) (COM2-3 RJ-45, Full Signal) 5 (COM4 RJ-11, Only TX/RX, 12V Power Output, Reserved for CDP) (COM5 Reserved for Cash Drawer Port) (COM6 RJ-45, Only TX/RX, 5V Power Output, Reserved for MSR)
LAN	1 x Gigabit Ethernet, RJ-45
Audio	1 x Line-out
Power DC-IN	J1900 1 x (4 Pin Connector) 6200U/4405U 1 x (3 Pin Connector)
Extension Slot	6200U/4405U mini PCIe, m-SATA

Power	
Power Supply	J1900 Adaptor 12V, 5A 6200U/4405U Adaptor 24V, 2A / 24V, 4A(Powered USB Option)
Physical & Environmental	
Operating Temperature	0°C ~ 60°C at 10% to 90% Humidity
Storage Temperature	-20°C ~ 80°C at 10% to 90% Humidity
Dimensions (W x H x D)	490 x 337 x 210(mm), 19.3 x 13.3 x 8.2(in)
Packing Dimensions (W x H x D)	640 x 465 x 300 (mm), 25.2 x 18.3 x 11.8(in)
Net Weight	9,000g, 19.8lbs
Packing Weight	10,200g, 22.5lbs
Certification	CE, FCC, KC(TBD),CB(TBD),CCC(TBD)
Color	Matt Dark Grey, High Gloss White

Options & Peripherals	
2nd Display	9.7", 12.1", 15" LCD Display, 1024 x 768, Optional Touchscreen
Customer Display	VFD, 20 Columns x 2 Lines J1900 1 x COM5 (RJ-45 8 Pins) (Factory Option) 1 x Cash Drawer Port (Factory Option) 6200U/4405U 1 x COM5 (RJ-45 8 Pins) (Factory Option) 1 x Cash Drawer Port (Factory Option) 1 x Powered USB (24V)
I/O Expansion	Storage 2.5 inch SSD 128GB, HDD 500GB, 1TB Magnetic Stripe Reader Comply with ISO 7811, Support 1 & 2 & 3 Track Smart Card Reader EMV Level 1, 2 (TBD) Dallas Dallas i-button Reader (TBD) Fingerprint Yes Wall Mount Kit VESA-Compatible, 75 x 75(mm), 100 x 100(mm) Serial Conversion Cable RJ-45 to D-sub 9 Speaker 2 x 0.8W (Stereo) (Factory Option)
WiFi	J1900 USB to WiFi Module (Factory Option) 6200U/4405U USB to WiFi Module (Factory Option), Mini PCIe for Wireless LAN

\*Other mounting options available upon request. \*Specifications may change without prior notice.

## 可选配件



### 客户显示器

- VFD (2 Lines x 20 Characters)



### 第二显示器

- 9.7", 12.1", 15" LCD



### 多种阅读器



- MSR, SCR



### POS 打印机

- A7, A11

## 尺寸



# POSBANK®

## Headquarters

#805~808, 108, Gasan digital 2-ro,  
Geumcheon-gu, Seoul, 08506, South Korea  
Tel : +82-2-2626-9118  
Fax : +82-2-2626-9119  
e-mail : sales@posbank.com  
www.posbank.com

## US

California : 1230 East 223rd Street, Suite #204  
Carson, CA 90745  
New York : 75 Fairchild Ave. Plainview  
New York 11803  
Tel : +1-888-998-1767 ext. 103~104  
Fax : +1-310-513-1362  
e-mail : sales@posbankusa.com  
www.posbankusa.com

## Europe

Via Piersanti Mattarella, 32, 30030, Gardigiano,  
Venezia, Italy  
Tel : +39-041-583-0594  
Fax : +39-041-583-0595  
e-mail : sales@posbank.eu  
www.posbank.eu

## 版权 © 2017 Posbank Co.,Ltd.

POSBANK和POSBANK的徽标是登记好的品牌在美国和其他的国家。所有的品牌是所有者的财产。INTEL,CELERON,CORE是登记好的品牌在美国和其他的国家。Microsoft, Windows 7, Windows 8.1, Windows 10和是Microsoft公司登记好的品牌在美国和其他的国家。关于剪辑的失误或者漏失, POSBANK没有负责。以信息目的可以用这发行物的信息和POSBANK可以修改或者变更。虽然没有通知, POSBANK的方向和用意可以变化或者取消。没有事先通知, 参数规格可以变更