

# APEXA® GL

## Compact Powerhouse™

Low-Power High-Performance Intel® Celeron® J1800 Quad-Core Processor  
معالج Intel® Celeron® J1800 رباعي النواة ، طاقة منخفضة وأداء عالي

15" Display with LED Backlight Delivering Bright and Crisp Images  
شاشة 15 إنش واضحة تماماً مع إضاءة LED ساطعة

Bezel-Free True-Flat PCAP Touch  
شاشة لمس مسطحة PCAP

Multiple I/O Interfaces for Peripherals  
مداخل ومخارج متعددة للإضافات

Engineered and Optimized for Hospitality and Retail Businesses  
تم صناعته ليتناسب مع قطاع الضيافة ومحلات البيع بالتجزئة



## Features & Benefits

## المميزات و الفوائد



### New Look. New Design مظهر جديد. تصميم جديد

Modern and Contemporary Styling  
حديث ومعاصر



### Powerful Performer أداء قوي

Low-Power High-Performance. Fanless Operation  
معالج قوي بطاقة منخفضة، بدون مروحة



### Superior Touch Display شاشة لمس رائعة

Bezel-Free True-Flat 15" LED LCD Display  
شاشة لمس مسطحة 15 إنش LED LCD



### Install It Anywhere ثبته في أي مكان

On a Counter or a Wall  
على منضدة أو جدار



### Save Time and Cost وفر الوقت والمال

Easy Access to I/O Interfaces  
مداخل ومخارج سهل الوصول إليها



### Connect It to All أوصل كل شيء

6 USB, 5 Serial. Optional Expansion Available  
إضافات اختيارية متوفرة، Serial 5, USB 6

## Specifications

## المواصفات التقنية

General Specifications		Model : J19
System		
CPU	Intel® Celeron® J1800 (2.0 GHz) Quad-Core Processor / Fanless	
Chipset	ITE IT8786-1	
Storage	SATA 2 (3Gb/s) 2.5 inch SSD 64GB, Support AHCI	
Memory	4GB Standard (Max. 8GB) Type: DDR3L 1333 MT/s / Socket 1 x SODIMM	
Graphics Controller	Integrated Intel HD Graphics	
Audio	Realtek ALC662-VD 5.1 CH Audio	
LCD Display		
Size / Type	15" TFT LED Backlight	
Resolution	1024 x 768	
Luminance	300 cd/m <sup>2</sup> (typ.)	
Touch Screen		
Type	Projective Capacitive Touch	
Controller Interface	USB Interface	
I/O Interface		
Display Port	1 x VGA (With 12V power output)	
USB Port	6 (Rear 2, Back 4 / USB 2.0 x 6 Ports), USB A type 1 (Rear 1, Reserved for MSR/SCR/I-Button), RJ-45 (COM 1 with 5V/12V power output on 9pins)	
Serial Port	5 (COM2~3 RJ-45 , Full Signal) (COM4 RJ-11, Only TX/RX, 12V power output, reserved for 2x20 Customer Display) (COM6 RJ-45, Only TX/RX, 5V power output, Reserved for MSR)	
Ethernet Port	RJ-45	
Audio	Line-out	
Power DC-IN	1 (4pins connector)	
Power Requirement		
Adapter Input	Adaptor 12V, 5A	

OS Support	
OS	Windows 7, Windows 8.1, POS Ready 7, Windows 10
Mechanical & Environmental	
Operating Temperature	0°C ~ 60°C at 10% ~ 90% humidity
Storage Temperature	-20°C ~ 80°C at 10% ~ 90% humidity
Color	Dark Grey, White
Dimensions (W x H x D)	364 x 333 x 210 (mm)
Net Weight	5,300g
Packing Dimension (W x H x D)	500 x 470 x 300 (mm)
Packing Weight	8,000g
Certification	CE, FCC, KC, CB, CCC

### Optional Configuration

Storage	2.5 inch SSD 128GB
	2.5 inch HDD 500GB
	2.5 inch HDD 1TB
I/O Expansion	1 x COM5 (RJ-45 8pins) (Factory Option)
	1 x Cash Drawer Port (RJ-11 6pins) (Factory Option)
Customer Display (CDP)	VFD (20 columns x 2 lines)
	9.7" 2nd LCD (1024 x 768 resolution)
	12.1" 2nd LCD (1024 x 768 Resolution)
2nd Display	15" 2nd LCD (1024 x 768 Resolution)
	15" 2nd LCD (1024 x 768 Resolution)
Magnetic Stripe Reader	MSR : Comply with ISO 7811, Support 1 & 2 & 3 track
Smart Card Reader	SCR : EMV level 1, 2
Dallas	Dallas I-button Reader
Camera	SM USB Interface (Internal) (Factory Option)
Wall Mount Kit	VESA-Compatible (75 x 75mm , 100 x 100mm)
Serial Conversion Cable	RJ-45 to D-sub 9

\*Other mounting options available upon request. \*Specifications may change without prior notice.

## Peripheral Options

## خيارات إضافية



**Customer Display**  
شاشة الزبون  
VFD (2 Lines x 20 Characters)



**2nd Display**  
شاشة عرض ثانية  
9.7", 12.1", 15" LCD



**Multi-Reader**  
قارئ متعدد  
MSR, SCR



**POS Printers**  
طابعات أرصدة  
A7, A11

## Dimension View

## الأبعاد

